## **Forklift Seat Belts**

Forklift Seat Belts - This guideline reason is to describe the Regulation necessities for the use of operator seatbelts or restraints on lift trucks. It is the employers' responsibility to ensure that every machine, piece of equipment and device in the workplace is chosen and utilized correctly and operated in accordance with the manufacturer's instructions.

With regards to their maintenance, inspection, fabrication, use and design Rough Terrain lift trucks should meet the guidelines of ANSI Standard ASME B56.6-1992.

Mobile equipment like for example side boom tractors with a Rollover Protective Structure (ROPS), have to have seat belts which meet the Society of Automotive Engineers safety requirements; Society of Automotive Engineers Standard J386 JUN93, Operator Restraint System for Off-Road Work Machines. If any mobile machine includes seat belts required by law, the driver and subsequent passengers have to make certain they make use of the belts every time the vehicle is in motion or engaged in operation as this can cause the machine to become unsteady and thus, unsafe.

If a seat belt or various operator restraint is required on a forklift.

While working a lift truck, the seat belt requirements would depend on several factors. Contributing factors to this determination might include whether or not the the forklift is equipped along with a Rollover Protective Structure, the kind of lift truck itself and the year the lift truck was actually made. The manufacturer's instructions and the requirements of the applicable standard are referenced in the Regulation.

With regards to to a driver restraint device, enclosure or system, ANSI Standard ASME B56.1-1993 regarding powered industrial trucks, is intended to be able to aid the driver in reducing the risk of entrapment of the head and/or torso between the truck and the ground in the event of a tip over. The system or restraint device might consist of a seat belt, while a seat belt is not essentially a part of such equipment or system.